

Paints & Finishes

Performance Specifications

CERAMIC

Must meet or exceed the LEED standards, must meet or exceed 3,000 scrub cycles on the ASTM D---2486 test, must contain Microban® Antimicrobial Product Protection (MCT proprietary Microban® formula does not contain triclosan --- a suspected carcinogen), be a one component EGGSHELL FINISH, and VOC's must be at or under 50 grams per liter

MICROTEX

Must meet or exceed the LEED standards, must meet or exceed 3,100 scrub cycles on the ASTM D---2486 test, must contain Microban® Antimicrobial Product Protection (MCT proprietary Microban® formula does not contain triclosan --- a suspected carcinogen), be a one component EGGSHELL FINISH and contain a black granulated additive, and VOC's must be at or under 50 grams per liter

LIQUAPEARL

Must meet or exceed the LEED standards, must meet or exceed 2,000 scrub cycles on the ASTM D---2486 test, must contain Microban® Antimicrobial Product Protection (MCT proprietary Microban® formula does not contain triclosan --- a suspected carcinogen), be a one component PEARLESCENT finish, VOC's must be at or under 150 grams per liter

SLATE FX

Must meet or exceed the LEED standards, must meet or exceed 3,100 scrub cycles on the ASTM D---2486 test, must contain Microban® Antimicrobial Product Protection (MCT proprietary Microban® formula does not contain triclosan --- a suspected carcinogen), be a one component EGGSHELL BASE COAT FINISH and a single component EFFECT COAT FINISH containing black granulates additive, and the VOC content must be at or under 50 grams per liter.